



Digital Poster 50in Outdoor Single-Sided Wall-Mounted 2500 nit



FHD Screen



Body Thickness Only 150mm



Easy Maintenance



IP65 Design
5mm Cover Glass
+2mm SPCC



1500/2000/2500nits
Sunlight Viewable
-40c to +50c



Android
Windows OS 7/8/10

Address: Lancaster Business Park, Burton upon Trent, DE13 9PD

Email: enquiries@projectdigitaluk.com

Website: projectdigitaluk.com

Technical Specifications

Digital Poster 50in Outdoor Single-Sided Wall-Mounted 2500 nit



Screen	50 Inch 16:9	Rich Resolution	Support 1080p,1080i,720p, 480p ^Multiple Resolutions
Panel Type	Samsung/Lg A-Si Lcd	Video Format Support	Mpeg1/Mpeg2/Mpeg4/Dh/X/Asp/WMV/AVI
Resolution	1920*1080 Dpi	Image Format Support	JPEG/BMP/Tiff/PNG/GIF
Display Area(WxH)	1073.78(H)*604(W) Mm	Audio Format Support	Wave/M P3/WMA/AAC
Product Size(WxHxD)	1300*870*100mm	Splicing Display	Support
Colour Depth	10bit(DJT L07billion Colours	Working Temperature	-30-50°
Viewing Angle	H178°/V178°	Working Humidity	-40%-55%
Brightness	2500 Cd/M2	Storage Temperature	(Tc-5ctc
Contrast Ratio	Typical:1100,Min:800	Storage Humidity	5%-95%
Backlit Type	WLED	Cooling	Air Conditioning
Response Time	6ms	Application Condition	Pure Outdoor All Weatherproof
Life(Hrs)	>60000 Hours	Material	Cold-Roll Steel Spcc
Power Supply	Ac 100-240v (50/60hz)	Frame Colour	Black/White/Silver/Customization
Standby/Max, Consumption	W3ww400w	Mount/Installation Type	Standing,iPhone Seamless Design
Control Method	Depends On The Follow Board Selected	Packing Way	Safe Packing With Bubble Foam, In Wooden Case
Colour System Support	Pal/Ntsc/Secam	Quality Standard	Iso9001,Ce(Rohs,Fcctccc
OSD Language	English/Multiple Language	Touch Method	Capacitive Touch
System Configuration:	Android7.1 4+16		

